



(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
14.07.1999 Bulletin 1999/28

(51) Int. Cl.⁶: **G01V 3/08**

(21) Application number: **98310218.7**

(22) Date of filing: **14.12.1998**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
 Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **09.01.1998 US 4834**

(71) Applicant:
International Business Machines
Corporation
Armonk, N.Y. 10504 (US)

(72) Inventor: **Koch, Roger Hilsen**
Amawalk, New York 10501 (US)

(74) Representative: **Boyce, Conor**
IBM United Kingdom Limited,
Intellectual Property Law,
Hursley Park
Winchester, Hampshire SO21 2JN (GB)

(54) Magnetic catheter tracker and method therefor

(57) A method and system for tracking an object (3) within a volume, includes coupling a rotating magnetic dipole (2) to the object (3), measuring (4) the magnetic fields either remotely, on the surface of, or exterior to the volume, to produce measurements; and based on the

measurements, determining the position and the orientation of the magnetic dipole (2), thereby to determine a position and orientation of the object (3).




FIG. 1A

Description

[0001] The present invention generally relates to a system, apparatus and method for tracking an object in a body or region, and more particularly to a system, apparatus and method for determining the position and orientation of a probe, such as a catheter, in a volume such as a human body by tracking the position of a rotating magnet or oscillating magnetic dipole that is placed in or on the probe or catheter.

[0002] Generally, with the existing technology and techniques, it has been very difficult to locate in three dimensions an object in a three-dimensional volume. Most conventional systems use separate two-dimensional images of an area of interest. However, the exact relative positions of the separate images are unknown, because the accuracy of the conventional methods for determining the location of the images is poor. Hence, finding an object in a three-dimensional volume, such as a human body, has been difficult, if not impossible, with the conventional techniques.

[0003] In many surgical procedures, physicians must insert probes (e.g., catheters) into the human body, and later must detect the position of the catheters for additional treatment, investigation, manipulation, removal from the body, etc.

[0004] Typically, the positions of the catheters are measured using a simple x-ray imaging system such as a fluoroscope or the like. However, this system images primarily in two dimensions (e.g., as shown in Figure 2) and is incapable of indicating the exact angular orientation of the catheter around its long axis. Precise quantitative information of the position of the catheter in the three spatial dimensions and the three orientation angles would be of great benefit.

[0005] For example, when a physician uses an ultrasonic transducer mounted on the rotating tip of a catheter imager to image the plaque in a person's arteries near or around the heart, the physician receives a series of two-dimensional images from the ultrasonic imager as the catheter is pulled through the blood vessels. However, the exact relative positions of the separate images are unknown, because the accuracy of the present methods for determining the location of the images is poor and incapable of measuring the orientation angles of the catheter. In any application where catheters or instruments must be placed into or next to the human body in a medical procedure, precise quantitative information of the precise location and angle of each probe would be of great value.

[0006] Moreover, extending beyond the problem of tracking a catheter in the human body, there are many situations where measuring the exact position and orientation of an object using remote sensors would be highly beneficial.

[0007] According to the present invention, there is provided a method of tracking an object according to claim 1 and a system for tracking an object in a volume

according to claim 11.

[0008] The invention provides a system, and method for accurately tracking a probe (e.g., catheter) in a three-dimensional continuum by either utilizing a pre-existing rotating motion of the probe (or by adding a rotating motion to the same), and attaching a small permanent magnet to the probe.

[0009] Preferably, an extremely small (e.g., approximately $1-2 \text{ mm}^2$) but powerful (e.g., on the order of about $10^{-2} \text{ Amp} \cdot \text{m}^2$) rare-earth magnet is positioned on a probe or the tip of a catheter.

[0010] With the present invention, the tip of the probe or catheter must rotate (or be made to rotate) around some axis. Such an alteration of the probe or catheter is inexpensive and relatively simple on those probes or catheters that already have such a rotating motion. Rotating motion could be added to those probes or catheters that do not already rotate (e.g., through a motor or the like), which again would be an inexpensive and simple retro-fit in many situations.

[0011] When the probe or catheter is in the volume or body of interest, magnetic field sensors placed around the volume, or next to the body, record the magnetic fields generated by the rotating magnet on the probe or catheter.

[0012] Using the outputs of the magnetic field sensors, mathematical algorithms and a computer/processor can determine the exact position and orientation of the magnet, and hence the exact position and orientation of the probe or catheter. This allows exact positional information to be recorded as the probe or catheter is moved.

[0013] Preferably, the invention provides a system and method for accurately tracking the position a rotating ultrasonic catheter in a human body by using magnetic tracking.

[0014] For an ultrasonic catheter, the computer constructs a three-dimensional image of all the separate two-dimensional ultrasonic images obtained from the imager.

[0015] Thus, with the present invention, a magnet is attached to the tip of a catheter, and when this catheter is placed inside the body (e.g., blood vessels), magnetic field measurements exterior to the body can accurately determine the position and orientation of the magnet, and, hence the position and orientation of the catheter.

[0016] Embodiments of the invention will now be described with reference to the accompanying drawings, in which:

Figure 1A is a block diagram illustrating a system for tracking an object according to the present invention;

Figure 1B illustrates a coordinate system for use with the present invention;

Figure 2 illustrates a schematic, two-dimensional

image of an artery from an ultrasonic imager;

Figure 3 illustrates a schematic, three-dimensional image using the system and method according to the present invention;

Figure 4 illustrates a schematic digital lock-in for a computer 8 according to the present invention; and

Figure 5 is a flowchart of the steps of the process (e.g., an inversion method) for tracking the object in a body according to the present invention.

[0017] Referring now to the drawings, and more particularly to Figure 1A, there is shown a block diagram of the system for tracking an object (e.g., such as a catheter) in a body (e.g., such as the human body).

[0018] As shown in Figure 1A, a system 1 is provided for tracking a magnetic dipole 2 attached to a first end (e.g., tip) of an elongated probe (e.g., a catheter in the exemplary application) 3. For example, the magnetic dipole preferably includes a rotating permanent magnet. The magnet is preferably extremely small (e.g., approximately $1\text{-}2\text{ mm}^2$) but powerful (e.g., on the order of about $10^{-2}\text{ Amp} \cdot \text{m}^2$) rare-earth magnet is positioned on a probe. While not as preferred for the present invention as the rotating rare earth magnet, it is conceivable that an electromagnet with a constant current, an electromagnet with an alternating current applied thereto, or the like could be used with suitable modifications, as would be known by one of ordinary skill in the art taking the present specification as a whole.

[0019] A second end of the catheter 3 is for insertion into a body of interest (e.g., a human body). The catheter 3 may have any diameter. For example, in one implementation, the catheter 3 has an outer diameter of 1 mm.

[0020] As shown in Figure 1A, the present invention measures the magnetic field at a plurality (e.g., two or more) of positions. The measurements are made with a magnetic sensing device (e.g., magnetometer) 4, such as a SQUID, a flux gate, a magneto-resistive sensor, a hall probe, or the like. Preferably, a 3-axes magnetometer is used as the magnetic sensing device. However, configurations are possible with 1-, 2-, or 3-axis (or more) sensors. However, a sensor having 3 axes is preferred, with a 6-coordinate display being shown in Figure 1B.

[0021] In the implementation shown in Figure 1A, the magnetometers 4 are preferably mounted in the corners of a substrate or in other suitable positions based on operating characteristics and designer constraints.

[0022] It is noted that while four magnetometers are shown in Figure 1B, only two magnetometers are needed to localize the rotating magnet 2. Hence, any configuration of stationary magnetic sensors could be used. An algorithm used by the present invention allows an arbitrary orientation, and/or positioning, but requires

at least two magnetometers to be placed at different positions. As mentioned above, the magnetometers preferably comprise a three-axes magnetometer.

[0023] The outputs of the magnetometers 4, representing the values of the magnetic fields, are provided to a control box 5 for operating the magnetometers. The control box 5 is available commercially, or alternatively may be constructed by one of ordinary skill in the art by assembling standard electronics for operating the magnetometers.

[0024] It is noted that there are three outputs for each magnetometer 4 (although only one is shown for convenience and brevity in Figure 1A). In other words, in the system as shown in Figure 1A, there are 12 outputs total, since there are provided four magnetometers 4.

[0025] The outputs of the control box 5 are filtered by filters 6. Specifically, a filter box 6 including a plurality of filters is for providing a band pass around the rotational frequency of the magnet, which helps reduce environmental noise signals from affecting the output of the tracker.

[0026] The output of the control box 5 represents the oscillating magnetic field that each of the magnetic sensors 4 is recording.

[0027] Filters 6 preferably comprise a band-pass filter at the rotational frequency of the magnet. Preferably, there is a filter 6 provided corresponding to each magnetic sensor 4. Also, there can be a gain in the filter box electronics (e.g., typically a gain of about 10 to 100, but of course any gain can be provided depending upon the designer's constraints and requirements).

[0028] Thereafter, the output of the filters 6 is digitized by an analog-to-digital (A/D) converter 7, in order to input digital values representing the magnetic fields into a computer (processor) 8.

[0029] It is noted that a motor 20 is preferably provided for rotating the magnet 2. The motor 20 also provides an AC reference synchronization signal (e.g., for synchronization with the magnet) to the A/D converter 7. The motor 20 is provided on one end of the probe (catheter), and the magnet is provided on the other end of the probe, as shown in Figure 1B.

[0030] As mentioned above, a schematic two-dimensional image of an artery wall 20 from an ultrasonic imager (e.g. 10 as shown in Figure 1) is shown in Figure 2. Such a two-dimensional schematic is similar to that provided by the conventional systems and techniques. The artery wall includes plaque 21 formed thereon, thereby reducing the cross-sectional area of the artery for carrying blood 22. Heart tissue 23 is shown surrounding the artery in this exemplary application.

[0031] In contrast to the schematic image of Figure 2, a schematic three-dimensional image using a rotating magnetic tracking (e.g., made possible by the rotating shaft 9 coupled to the catheter 3 as shown in Figure 1A) according to the present invention is shown in Figure 3. As shown, the positioning of the catheter is made much more accurate with the rotating tracking method and

positioning of the catheter 3 in regard to an artery 30 and the plaque build-up 31 therein can be detected reliably and accurately.

[0032] As shown in Figure 4, the architecture of the computer 8 preferably comprises a direct current (DC) level shifter (subtractor) 40 to reduce the offset from zero of the average magnetic field, a digital lock-in unit 50 (preferably approximated in software for each of the input channels), and an algorithm processor 60 for performing the inventive algorithm, and specifically the inversion method discussed below, to select/provide a result. It is noted that, while the digital lock-in unit 50 preferably is approximated in software according to the present invention, the digital lock-in unit alternatively could be provided in hardware as would be known by one of ordinary skill in the art taking the present invention as a whole.

[0033] The digital lock-in is achieved by recording a reference signal from the rotating magnet synchronously with the rotating magnet 2. The signals from the magnetometers and the reference signals are input to the DC level shifter 40, as mentioned above, and then outputs are provided to a multiplier 51 of the digital lock-in 50.

[0034] An output from the multiplier is provided to a low pass filter 52 and filtered. Thereafter, an averaging unit 53 averages the outputs from the low pass filter 52, and provides an output. Typically, averaging unit 53 will provide 6-12 outputs (e.g., 3/magnetometer) depending upon the number of magnetometers. The outputs from the averaging unit 53 represents an estimate of the magnetic field from the respective magnets 2.

[0035] Thereafter, the outputs are input to the algorithm processor 60 which selects a result based on an inversion method, as discussed below with reference to Figure 5. The result of the processor 60 is output to a display (e.g., cathode ray tube (CRT) monitor, printer, etc.) 70, if desired. It is noted that the display 70 does not constitute a component of the architecture of the computer 8.

[0036] Referring now to Figure 5, the inversion method performed by the algorithm processor 60 is described.

[0037] First, in step 501, the magnetometer with the largest magnetic field is found based on the values (e.g., 6 to 12 values) provided by the averaging unit 53. Such a process can be performed by comparing each of the values to one another and selecting the largest value, and storing the same.

[0038] Then, in step 502, the coordinate system is rotated so that the vector field lies in two direction for that vector (e.g., see the coordinate system of Figure 1B). Using polar coordinates, only the ϕ and θ values are unknown.

[0039] Finally, in step 503, the ϕ and θ values are iteratively searched to find the best location. The best location will be the value with the smallest "metric" (e.g., smallest deviation between the predicted field and the

measured field). Thus, the metric represents the "goodness of fit". Specifically, to find the "metric", the following equation is used:

$$metric = \sqrt{\sum (B_{pred} - B_{meas})^2}$$

[0040] The operation and tracking algorithm used by the computer 8 are described below.

[0041] In operation, the computer 8 (e.g., multiplier 51) multiplies the input signal of each of the magnetic sensors 4 by a reference signal from the rotating magnet 2 to produce a dc level which corresponds to the average magnetic field for that sensor 4 at the rotational frequency. This concept is exactly that of a lock-in implemented digitally.

[0042] Thereafter, the output of the digital lock-in can be used with the inversion algorithm (e.g., inversion method), to convert the measured magnetic fields into the position of the magnet 2.

[0043] Using the values of the magnetic fields at the measurement positions, the computer inversion algorithm converts the magnetic field values into a value representing the position of the magnet 2.

[0044] Hereinbelow, one cycle of the operation of attaching the magnet to the catheter 3, insertion of the catheter into the body, and then taking a measurement of the position of the catheter, is described.

[0045] The operation of the system is quite simple. First, the magnet is attached to the catheter, and then the catheter is placed into the human body. The catheter is normally rotated in order to make an ultrasonic measurement.

[0046] Then, the sensor platform holding the sensors 4 is placed near the body, and, by using the above described electronics and algorithm, the position of the rotating magnet, and hence the tip of the sensor, can be determined.

[0047] It is noted that, while such a measurement above may be made with the magnet affixed directly to the catheter, the technique according to the present invention works significantly better for catheters which allow the magnet to be attached to a rotating flexible shaft 9 within the catheter 3. Such catheters 3 are typically used to image ultrasonically the insides of blood vessels and arteries around the heart or in the urinary track. Such rotation is made possible, for example, by the motor 20 mentioned above.

[0048] As mentioned above, the three-dimensional imaging provided by the rotating magnet tracking of the present invention is highly accurate as compared to the two-dimensional imaging of the conventional techniques.

[0049] Thus, rotating magnet tracking is advantageous in that it inexpensively provides instantaneous and exact positional information of the location of the catheter 3. Such instantaneous and exact positional location is obtained without the need for an accurate dc measurement of the magnetic field of the hospital room

before the catheter is introduced, as in a non-rotating source. Additionally, the rotating source tracking can be performed easily in an ordinary hospital environment.

[0050] With the invention, costs are minimized since an extremely small rare earth magnet is positioned on a tip of a catheter which is an inexpensive and minimal alteration of the catheter. Further, the reliability and accuracy of the measurement are high, as compared to the conventional systems.

Claims

1. A method of tracking an object within a volume, the method comprising steps of:

coupling a rotating magnetic dipole to said object.

measuring magnetic fields produced by the rotating magnetic dipole, to produce measurements; and

based on said measurements, determining a position and an orientation of the rotating magnetic dipole, thereby to determine a position of said object.

2. The method according to claim 1, wherein said step of measuring magnetic fields produced by the magnetic dipole comprises one of measuring the magnetic fields remotely, on the surface of the volume and exterior to the volume, to produce said measurements.

3. The method according to claim 1, wherein said step of determining comprises:

inputting said measurements to a processor, said measurements comprising signals representing values of the magnetic fields:

filtering said signals to produce filtered signals; and

digitizing said filtered signals.

4. The method according to claim 3, said step of determining further comprising:

recording a reference signal from the rotating magnetic dipole synchronously with the rotating magnetic dipole;

performing a direct current (DC) level shift of said digitized signals and the reference signal, to reduce an offset from zero of an average magnetic field and produced a level-shifted value; and

performing a digital lock-in operation based on said level-shifted value.

5. The method according to claim 4, wherein said digital lock-in operation comprises:

multiplying each of said level-shifted values by a reference signal from the rotating magnet to produce a dc level which corresponds to the average magnetic field for a respective sensor at a rotational frequency, to produce multiplied values;

filtering said multiplied values by a low pass filter; and

averaging said multiplied values having been filtered, to provide average outputs, said average outputs representing estimates of the magnetic fields.

6. The method according to claim 5, further comprising processing to select a result, said step of processing comprising:

performing an inversion method, said inversion method comprising:

based on said multiplied values having been filtered, identifying a magnetic sensor having a largest magnetic field;

rotating a coordinate system of the magnetic sensor having the largest magnetic field such that a vector field thereof lies in two directions;

using polar coordinates, iteratively searching for a combination of ϕ and θ values which provide a smallest deviation between a predicted magnetic field and a measured magnetic field so to convert the magnetic fields into a position of the rotating magnet.

7. The method according to claim 1 wherein the volume is a human body, said magnetic dipole is a rare-earth magnet and said step of measuring magnetic fields comprises one of measuring the magnetic fields remotely, exterior to the body, to produce measurements.

8. The method according to claim 1 or 7, wherein said step of determining comprises:

inputting said measurements into a processor, and said processor performing calculations to determine a position of the magnet.

9. The method according to claim 8, wherein said step

of coupling said magnet to said object comprises coupling said magnet to a catheter for insertion into the volume.

10. The method according to claim 1 or 7, further comprising a step of: 5

coupling a rotating shaft to said object, thereby providing a rotating tracking of said object.

10

11. A system for tracking an object in a volume, comprising:

a rotating magnet coupled to said object;

15

a detector for measuring magnetic fields exterior to the volume produced by said rotating magnet, to produce measurements; and

a determining unit for determining, based on said measurements, a position of the magnet, thereby to determine a position of said object. 20

12. The system according to claim 11, wherein said detector comprises at least two magnetometers, each of said at least two magnetometers comprising a three-axes magnetometer. 25

13. The system according to claim 11, wherein said detector comprises at least two magnetometers for localizing the rotating magnet, said at least two magnetometers each comprising a three-axes magnetometer, each magnetometer providing three outputs thereof. 30

35

14. The system according to claim 11, wherein at least two detectors are provided,

said system further comprising a bandpass filter for filtering outputs from said at least two detectors, thereby providing a band pass around a rotational frequency of the magnet, a filter being provided corresponding to each said at least two detectors; 40

45

an analog-to-digital (A/D) converter for converting filtered outputs from said filter to digital values representing the magnetic fields, said digital values being inputted into said determining unit, said determining unit comprising a computer. 50

15. The system according to claim 14, further comprising:

55

a motor for rotating said magnet, and for providing an alternating current (AC) reference synchronization signal to said A/D converter.




FIG. 1A




FIG. 1B

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 928 976 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
21.11.2001 Bulletin 2001/47

(51) Int Cl.7: **G01V 3/08**

(43) Date of publication A2:
14.07.1999 Bulletin 1999/28

(21) Application number: **98310218.7**

(22) Date of filing: **14.12.1998**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Koch, Roger Hilsen**
Amawalk, New York 10501 (US)

(74) Representative: **Boyce, Conor**
IBM United Kingdom Limited,
Intellectual Property Law,
Hursley Park
Winchester, Hampshire SO21 2JN (GB)


(30) Priority: **09.01.1998 US 4834**

(71) Applicant: **International Business Machines
Corporation**
Armonk, NY 10504 (US)

(54) **Magnetic catheter tracker and method therefor**

(57) A method and system for tracking an object (3) within a volume, includes coupling a rotating magnetic dipole (2) to the object (3), measuring (4) the magnetic fields either remotely, on the surface of, or exterior to

the volume, to produce measurements; and based on the measurements, determining the position and the orientation of the magnetic dipole (2), thereby to determine a position and orientation of the object (3).



EP 0 928 976 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 31 0218

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	US 5 425 382 A (GOLDEN ROBERT N ET AL) 20 June 1995 (1995-06-20) * column 5, line 37 - line 54 * * column 6, line 58 - line 62 * * column 7, line 54 - column 8, line 11 * * figures 1,2 *	1-3,7-12	G01V3/08
X	US 5 425 367 A (STROHL JR CLAIR L ET AL) 20 June 1995 (1995-06-20) * column 2, line 41 - column 3, line 5 * * figures 3,4 *	1-3,11	
X	US 5 014 008 A (FLOWERDEW PETER M) 7 May 1991 (1991-05-07) * column 2, line 10 - line 28 *	1,2,11	
X	WO 97 49445 A (SOMOGYI CHRISTOPHER P ;GOLDEN ROBERT N (US); LUCENT MEDICAL SYSTEM) 31 December 1997 (1997-12-31) * page 16, line 4 - line 18 *	1,2,11	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			G01V A61B A61M
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 14 September 2001	Examiner Modesto, C
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document</p> <p>T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons & member of the same patent family, corresponding document</p>			

EP 0 928 976 A3 (01/01/01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP. 98 31 0218

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

14-09-2001

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5425382	A	20-06-1995	AU 716011 B2	17-02-2000
			AU 5269898 A	19-03-1998
			AU 689136 B2	26-03-1998
			AU 7835694 A	03-04-1995
			CA 2171717 A1	23-03-1995
			DE 69421820 D1	30-12-1999
			DE 69421820 T2	16-03-2000
			DK 719420 T3	01-05-2000
			EP 0719420 A1	03-07-1996
			ES 2141257 T3	16-03-2000
			JP 9503054 T	25-03-1997
			WO 9508130 A1	23-03-1995
			US 5622169 A	22-04-1997
			US 5902238 A	11-05-1999
US 5425367	A	20-06-1995	AU 666672 B2	22-02-1996
			AU 2511592 A	05-04-1993
			CA 2116970 A1	18-03-1993
			EP 0606253 A1	20-07-1994
			JP 7500979 T	02-02-1995
			WO 9304628 A1	18-03-1993
			US 5645065 A	08-07-1997
US 5014008	A	07-05-1991	WO 9000259 A1	11-01-1990
			GB 2220070 A	28-12-1989
			GB 2230342 A ,B	17-10-1990
			JP 3500212 T	17-01-1991
WO 9749445	A	31-12-1997	US 5775322 A	07-07-1998
			AU 3313697 A	14-01-1998
			WO 9749445 A1	31-12-1997